

Laminates:  
 FRP - Fiber Reinforced Plastic  
 Poly - High Density Poly  
 Alum - Aluminum  
 SS - Stainless Steel



Pb - Pebbled  
 Sm - Smooth  
 Emb - Embossed  
 PF - Protective Film  
 FR - Fire Rated Class 1  
 2S - 2 Sides  
 NA - Not Available  
 SO - Special Order  
 Bkr - Backer  
 Sq Ft - Square Foot  
 Wt. - Weight  
 \* - FRP Surface Seal Finish

## XPS Laminated Panels

Extruded Polystyrene Foam

Product Number	Surface Laminate	Backer Substrate 2lb Density	4' X 8'	4' X 10'	4' X 12'	Sq. Ft. Weight Lb.
2235.7510	.035 Pb FRP	1" Sanded				.46
2235.7510 .2235	.035 Pb FRP 2S	1" Sanded				.71
2135.7510	.035 Sm FRP	1" Sanded				.51
2135.7510 .2135	.035 Sm FRP 2S	1" Sanded				.81
2250.7510	.050 Pb FRP*	1" Sanded				.61
2250.7510 .1113	.050 Pb FRP* .013 Alum Bkr	1" Sanded				.82
2290.7510	.090 Pb FRP	1" Sanded				.86
2190.7510	.090 Sm FRP	1" Sanded				.91
2290.7510	.090 Pb FRP-FR	1" Sanded				.86
1113.7510 .1113	.013 Sm Alum 2S	1" Sanded				.64
1124.7510 .1113	.024 Sm Alum .013 Alum Bkr	1" Sanded				.76
1718.7510	.018 SS	1" Sanded				.95
1718.7510 .1113	.018 SS .013 Alum Bkr	1" Sanded				1.16

Different Thicknesses, sizes and foam Densities are available  
 Foam meets ASTM C578 type 4  
 Foam R Value = 5 per inch of thickness



**Laminates:**  
 FRP - Fiber Reinforced Plastic  
 Poly - High Density Poly  
 Alum - Aluminum  
 SS - Stainless Steel

Pb - Pebbled  
 Sm - Smooth  
 Emb - Embossed  
 PF - Protective Film  
 FR - Fire Rated Class 1  
 2S - 2 Sides  
 NA - Not Available  
 SO - Special Order  
 Bkr - Backer  
 Sq Ft - Square Foot  
 Wt. - Weight  
 \* - FRP Surface Seal Finish

## XPS Laminated Panels Extruded Polystyrene Foam

Product Number	Surface Laminate	Backer Substrate 2 lb Density	4' X 8'	4' X 10'	4' X 12'	Sq. Ft. Weight Lb.
2235.7520	.035 Pb FRP	2" Sanded				.66
2235.7520 .2235	.035 Pb FRP 2S	2" Sanded				.91
2135.7520	.035 Sm FRP	2" Sanded				.71
2135.7520 .2135	.035 Sm FRP 2S	2" Sanded				1.01
2250.7520	.050 Pb FRP*	2" Sanded				.81
2250.7520 .1113	.050 Pb FRP* .013 Alum Bkr	2" Sanded				1.02
2290.7520	.090 Pb FRP	2" Sanded				1.06
2190.7520	.090 Sm FRP	2" Sanded				1.11
2290.7520	.090 Pb FRP-FR	2" Sanded				1.06
1113.7520 .1113	.013 Sm Alum 2S	2" Sanded				.84
1124.7520 .1113	.024 Sm Alum .013 Alum Bkr	2" Sanded				.96
1718.7520	.018 SS	2" Sanded				1.15
1718.7520 .1113	.018 SS .013 Alum Bkr	2" Sanded				1.36

Different Thicknesses, sizes and foam Densities are available  
 Foam meets ASTM C578 type 4  
 Foam R Value = 5 per inch of thickness